

# SCHMIDT BENDER

## 1-8x24 PM II ShortDot Dual CC



8  
ZOOM

30  
mm



ZC  
ZERO CLICK  
ILLUMINATION

D  
DIFFRACTIVE

CC  
CLOSE  
COMBAT  
MODE

MTC  
MORE  
FACTILE  
CLICKS

LT  
LOCKING  
TURRETS

ZC  
ZERO CLICK

RAL  
COLOR YOUR  
SCOPE

THROW LEVER  
COMPATIBLE

-46°C

25m  
WATERPROOF

WINNER OF  
THE G28  
CONTRACT



**Bundeswehr**

- Reticle in the 1<sup>st</sup> and RedDot in the 2<sup>nd</sup> focal plane
- In CC-Mode parallax free at close distances
- Lockable elevation and windage turret

For more Information about Schmidt & Bender products visit [www.schmidt-bender.com](http://www.schmidt-bender.com)

# SCHMIDT BENDER

## 1-8x24 PM II ShortDot Dual CC



### 1. Dimensions & properties\*

Weight:	630 g
Length:	293 mm
Main tube diameter:	30 mm

### 2. Optical Data\*

Magnification:	1.0-8.0
Objective diameter:	24 mm
Field of view:	35.3 m-4.9 m/100 m
Exit pupil:	9.8 mm-3.0 mm
Eye relief:	90 mm
Twilight factor:	3.4-13.9
Transmission:	>90 %
Focal plane:	1/2

### 3. Adjustments\*

Diopter:	-3 dpt. to +2 dpt.
Adjustment range elevation turret:	120 cm/100 m
Adjustment range windage turret:	±60 cm/100 m
Parallax:	100 m fix (7 m CC)

### 4. Available configurations\*

#### a.) Turrets:

Elevation: Single turn with MTC and locking function

Windage: Single turn with ZC and locking function

Turret configurations:

Elevation	Windage
1 cm cw	1 cm cw
1 cm ccw	1 cm ccw

#### b.) Colors:

• Black · RAL 8000 · Pantone 7504M

#### c.) Illumination

- Illuminated Reticle
- Diffractive RedDot

#### d.) Reticles

- MDR-T6 · MDR
- Others on request

e.) Other configurations available on request

\* all data is subject to change

